



A-Class Saloon A 160 CDI.

Engine and performance (AUTOTRONIC (CVT))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.991
Rated output (35) 1)	60 /4.200
Rated torque (Nm @ rpm) 1)	200/1.400 - 2.600
Compression ratio	18,0 : 1
Acceleration 0-100 km/h (s)	15,3
Top speed (km/h)	165

Power transmission (AUTOTRONIC (CVT))	
Drive system	Front-wheel drive
Transmission	AUTOTRONIC (CVT)
Ratios	2,72/1,71/1,19/0,91/0,72/0,55/0,42/R1 4,22/R2 -
Final-drive ratio	3,95

Fuel and emissions (AUTOTRONIC (CVT))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	7,0-7,6
Fuel consumption, extra-urban (l/100km) 2)	4,4-4,9
Fuel consumption, combined (l/100km) 2)	5,4-5,8
CO2 emissions combined (g/km) 2)	142-154
Cd value	0,30
Emissions category	Euro 5

Chassis and steering	
Front axle	Spring strut+wishbone
Rear axle	Parabolic axle
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	185/65 R 15 88 T
Tyres/wheels, rear	185/65 R 15 88 T
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Quantities, dimensions and weights (AUTOTRONIC (CVT))	
Kerb weight/payload (kg) 3)	1.370/465
Perm. gross vehicle weight (kg)	1.835
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	645 / 1.000

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently



Mercedes-Benz

A-Class Saloon A 160 CDI.

applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



A-Class Saloon A 160 CDI BlueEFFICIENCY.

Engine and performance (5-speed (manual))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.991
Rated output (35) 1)	60 /4.200
Rated torque (Nm @ rpm) 1)	180/1.400 - 2.600
Compression ratio	18,0 : 1
Acceleration 0-100 km/h (s)	15,0
Top speed (km/h)	170

Power transmission (5-speed (manual))	
Drive system	Front-wheel drive
Transmission	5-speed (manual)
Ratios	3,64/2,04/1,26/0,88/0,70/-/-/R1 3,29/R2 -
Final-drive ratio	3,32

Fuel and emissions (5-speed (manual))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	5,4-5,8
Fuel consumption, extra-urban (l/100km) 2)	3,9-4,1
Fuel consumption, combined (l/100km) 2)	4,5-4,7
CO2 emissions combined (g/km) 2)	118-125
Cd value	0,30
Emissions category	Euro 5

Chassis and steering	
Front axle	Spring strut+wishbone
Rear axle	Parabolic axle
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	185/65 R 15 88 T
Tyres/wheels, rear	185/65 R 15 88 T
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Quantities, dimensions and weights (5-speed (manual))	
Kerb weight/payload (kg) 3)	1.325/510
Perm. gross vehicle weight (kg)	1.835
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	-/-

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

A-Class Saloon A 160 CDI BlueEFFICIENCY.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



A-Class Saloon A 180 CDI.

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.991
Rated output (35) 1)	80 /4.200
Rated torque (Nm @ rpm) 1)	250/1.600 - 2.600
Compression ratio	18,0 : 1
Acceleration 0-100 km/h (s)	10,8
Top speed (km/h)	186

Engine and performance (AUTOTRONIC (CVT))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.991
Rated output (35) 1)	80 /4.200
Rated torque (Nm @ rpm) 1)	250/1.600 - 2.600
Compression ratio	18,0 : 1
Acceleration 0-100 km/h (s)	11,1
Top speed (km/h)	181

Power transmission (6-speed (manual))	
Drive system	Front-wheel drive
Transmission	6-speed (manual)
Ratios	12,74/7,20/4,50/3,16/2,50/2,20/-/R1 12,64/R2 -
Final-drive ratio	1,00

Power transmission (AUTOTRONIC (CVT))	
Drive system	Front-wheel drive
Transmission	AUTOTRONIC (CVT)
Ratios	2,72/1,80/1,25/0,90/0,69/0,53/0,42/R1 4,22/R2 -
Final-drive ratio	3,95

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	6,1-6,5
Fuel consumption, extra-urban (l/100km) 2)	4,2-4,4
Fuel consumption, combined (l/100km) 2)	4,9-5,2
CO2 emissions combined (g/km) 2)	128-138
Cd value	0,30
Emissions category	Euro 5

Fuel and emissions (AUTOTRONIC (CVT))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	7,0-7,6
Fuel consumption, extra-urban (l/100km) 2)	4,4-4,9
Fuel consumption, combined (l/100km) 2)	5,4-5,8
CO2 emissions combined (g/km) 2)	142-154
Cd value	0,30



A-Class Saloon A 180 CDI.

Emissions category	Euro 5
--------------------	--------

Chassis and steering	
Front axle	Spring strut+wishbone
Rear axle	Parabolic axle
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	185/65 R 15 88 T
Tyres/wheels, rear	185/65 R 15 88 T
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.355/485
Perm. gross vehicle weight (kg)	1.830
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	645/1.500

Quantities, dimensions and weights (AUTOTRONIC (CVT))	
Kerb weight/payload (kg) 3)	1.380/450
Perm. gross vehicle weight (kg)	1.830
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	645/1.500

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



A-Class Saloon A 200 CDI.

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.991
Rated output (35) 1)	103 /4.200
Rated torque (Nm @ rpm) 1)	300/1.600 - 3.000
Compression ratio	18,0 : 1
Acceleration 0-100 km/h (s)	9,5
Top speed (km/h)	201

Engine and performance (AUTOTRONIC (CVT))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.991
Rated output (35) 1)	103 /4.200
Rated torque (Nm @ rpm) 1)	280/1.600 - 3.000
Compression ratio	18,0 : 1
Acceleration 0-100 km/h (s)	9,6
Top speed (km/h)	196

Power transmission (6-speed (manual))	
Drive system	Front-wheel drive
Transmission	6-speed (manual)
Ratios	12,74/7,20/4,50/3,16/2,50/2,20/-/R1 12,64/R2 -
Final-drive ratio	1,00

Power transmission (AUTOTRONIC (CVT))	
Drive system	Front-wheel drive
Transmission	AUTOTRONIC (CVT)
Ratios	2,72/1,81/1,20/0,83/0,62/0,50/0,42/R1 4,22/R2 -
Final-drive ratio	3,95

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	6,5-6,6
Fuel consumption, extra-urban (l/100km) 2)	4,3-4,4
Fuel consumption, combined (l/100km) 2)	5,1-5,3
CO2 emissions combined (g/km) 2)	135-139
Cd value	0,30
Emissions category	Euro 5

Fuel and emissions (AUTOTRONIC (CVT))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	6,7-7,9
Fuel consumption, extra-urban (l/100km) 2)	4,8-5,0
Fuel consumption, combined (l/100km) 2)	5,5-6,0
CO2 emissions combined (g/km) 2)	144-159
Cd value	0,30



A-Class Saloon A 200 CDI.

Emissions category	Euro 5
--------------------	--------

Chassis and steering	
Front axle	Spring strut+wishbone
Rear axle	Parabolic axle
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	195/55 R 16 87 H
Tyres/wheels, rear	195/55 R 16 87 H
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.365/515
Perm. gross vehicle weight (kg)	1.880
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	645/1.500

Quantities, dimensions and weights (AUTOTRONIC (CVT))	
Kerb weight/payload (kg) 3)	1.395/485
Perm. gross vehicle weight (kg)	1.880
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	645/1.500

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



A-Class Saloon A 160.

Engine and performance (AUTOTRONIC (CVT))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.498
Rated output (35) 1)	70 /5.200
Rated torque (Nm @ rpm) 1)	140/3.500 - 4.000
Compression ratio	11,0 : 1
Acceleration 0-100 km/h (s)	13,5
Top speed (km/h)	170

Power transmission (AUTOTRONIC (CVT))	
Drive system	Front-wheel drive
Transmission	AUTOTRONIC (CVT)
Ratios	2,72/1,71/1,19/0,91/0,72/0,55/0,42/R1 4,22/R2 -
Final-drive ratio	4,86

Fuel and emissions (AUTOTRONIC (CVT))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	8,7-8,9
Fuel consumption, extra-urban (l/100km) 2)	5,7-6,2
Fuel consumption, combined (l/100km) 2)	6,8-7,2
CO2 emissions combined (g/km) 2)	159-168
Cd value	0,31
Emissions category	Euro 5

Chassis and steering	
Front axle	Spring strut+wishbone
Rear axle	Parabolic axle
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	185/65 R 15 88 T
Tyres/wheels, rear	185/65 R 15 88 T
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, solid
Rear brakes	Discs, solid

Quantities, dimensions and weights (AUTOTRONIC (CVT))	
Kerb weight/payload (kg) 3)	1.275/465
Perm. gross vehicle weight (kg)	1.740
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	595 / 1.000

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

A-Class Saloon A 160.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



A-Class Saloon A 160 BlueEFFICIENCY.

Engine and performance (5-speed (manual))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.498
Rated output (35) 1)	70 /5.200
Rated torque (Nm @ rpm) 1)	140/3.500 - 4.000
Compression ratio	11,0 : 1
Acceleration 0-100 km/h (s)	12,6
Top speed (km/h)	175

Power transmission (5-speed (manual))	
Drive system	Front-wheel drive
Transmission	5-speed (manual)
Ratios	3,64/2,04/1,33/1,03/0,82/-/-/R1 3,29/R2 -
Final-drive ratio	3,88

Fuel and emissions (5-speed (manual))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	7,5-7,8
Fuel consumption, extra-urban (l/100km) 2)	5,1-5,2
Fuel consumption, combined (l/100km) 2)	6,0-6,2
CO2 emissions combined (g/km) 2)	139-143
Cd value	0,31
Emissions category	Euro 5

Chassis and steering	
Front axle	Spring strut+wishbone
Rear axle	Parabolic axle
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	185/65 R 15 88 T
Tyres/wheels, rear	185/65 R 15 88 T
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, solid
Rear brakes	Discs, solid

Quantities, dimensions and weights (5-speed (manual))	
Kerb weight/payload (kg) 3)	1.245/495
Perm. gross vehicle weight (kg)	1.740
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	595 / 1.000

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

A-Class Saloon A 160 BlueEFFICIENCY.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



A-Class Saloon A 180.

Engine and performance (AUTOTRONIC (CVT))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.699
Rated output (35) 1)	85 /5.500
Rated torque (Nm @ rpm) 1)	155/3.500 - 4.000
Compression ratio	11,0 : 1
Acceleration 0-100 km/h (s)	11,5
Top speed (km/h)	183

Power transmission (AUTOTRONIC (CVT))	
Drive system	Front-wheel drive
Transmission	AUTOTRONIC (CVT)
Ratios	2,72/1,71/1,19/0,91/0,72/0,55/0,42/R1 4,22/R2 -
Final-drive ratio	4,86

Fuel and emissions (AUTOTRONIC (CVT))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	8,8-9,2
Fuel consumption, extra-urban (l/100km) 2)	5,7-6,2
Fuel consumption, combined (l/100km) 2)	6,8-7,3
CO2 emissions combined (g/km) 2)	159-171
Cd value	0,31
Emissions category	Euro 5

Chassis and steering	
Front axle	Spring strut+wishbone
Rear axle	Parabolic axle
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	185/65 R 15 88 T
Tyres/wheels, rear	185/65 R 15 88 T
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Quantities, dimensions and weights (AUTOTRONIC (CVT))	
Kerb weight/payload (kg) 3)	1.279/491
Perm. gross vehicle weight (kg)	1.770
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	595/1.300

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

A-Class Saloon A 180.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



A-Class Saloon A 180 BlueEFFICIENCY.

Engine and performance (5-speed (manual))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	1.699
Rated output (35) 1)	85 /5.500
Rated torque (Nm @ rpm) 1)	155/3.500 - 4.000
Compression ratio	11,0 : 1
Acceleration 0-100 km/h (s)	10,9
Top speed (km/h)	188

Power transmission (5-speed (manual))	
Drive system	Front-wheel drive
Transmission	5-speed (manual)
Ratios	3,64/2,04/1,33/1,03/0,82/-/-/R1 3,29/R2 -
Final-drive ratio	3,88

Fuel and emissions (5-speed (manual))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	8,1-8,2
Fuel consumption, extra-urban (l/100km) 2)	5,2-5,7
Fuel consumption, combined (l/100km) 2)	6,3-6,6
CO2 emissions combined (g/km) 2)	145-153
Cd value	0,31
Emissions category	Euro 5

Chassis and steering	
Front axle	Spring strut+wishbone
Rear axle	Parabolic axle
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	185/65 R 15 88 T
Tyres/wheels, rear	185/65 R 15 88 T
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Quantities, dimensions and weights (5-speed (manual))	
Kerb weight/payload (kg) 3)	1.260/510
Perm. gross vehicle weight (kg)	1.770
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	595/1.300

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

A-Class Saloon A 180 BlueEFFICIENCY.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



A-Class Saloon A 200.

Engine and performance (5-speed (manual))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	2.034
Rated output (35) 1)	100 /5.500
Rated torque (Nm @ rpm) 1)	185/3.500 - 4.000
Compression ratio	11,0 : 1
Acceleration 0-100 km/h (s)	9,8
Top speed (km/h)	200

Engine and performance (AUTOTRONIC (CVT))	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	2.034
Rated output (35) 1)	100 /5.500
Rated torque (Nm @ rpm) 1)	185/3.500 - 4.000
Compression ratio	11,0 : 1
Acceleration 0-100 km/h (s)	9,9
Top speed (km/h)	195

Power transmission (5-speed (manual))	
Drive system	Front-wheel drive
Transmission	5-speed (manual)
Ratios	3,64/2,04/1,33/1,03/0,82/-/-/R1 3,29/R2 -
Final-drive ratio	3,72

Power transmission (AUTOTRONIC (CVT))	
Drive system	Front-wheel drive
Transmission	AUTOTRONIC (CVT)
Ratios	2,72/1,77/1,20/0,90/0,65/0,52/0,42/R1 4,22/R2 -
Final-drive ratio	4,86

Fuel and emissions (5-speed (manual))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	8,7-8,9
Fuel consumption, extra-urban (l/100km) 2)	5,6-5,6
Fuel consumption, combined (l/100km) 2)	6,7-6,8
CO2 emissions combined (g/km) 2)	156-159
Cd value	0,31
Emissions category	Euro 5

Fuel and emissions (AUTOTRONIC (CVT))	
Tank capacity/reserve (l)	54/6
Fuel consumption, urban (l/100km) 2)	9,8-9,8
Fuel consumption, extra-urban (l/100km) 2)	6,1-6,3
Fuel consumption, combined (l/100km) 2)	7,4-7,6
CO2 emissions combined (g/km) 2)	174-178
Cd value	0,31



A-Class Saloon A 200.

Emissions category	Euro 5
--------------------	--------

Chassis and steering	
Front axle	Spring strut+wishbone
Rear axle	Parabolic axle
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	195/55 R 16 87 H
Tyres/wheels, rear	195/55 R 16 87 H
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Quantities, dimensions and weights (5-speed (manual))	
Kerb weight/payload (kg) 3)	1.270/495
Perm. gross vehicle weight (kg)	1.765
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	595/1.500

Quantities, dimensions and weights (AUTOTRONIC (CVT))	
Kerb weight/payload (kg) 3)	1.315/450
Perm. gross vehicle weight (kg)	1.765
Max. roof load (kg)	50
Boot capacity (VDA) (l)	435-1.370
Turning circle (m)	10,95
perm. trailer load, braked/unbraked (kg)	595/1.500

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly