



## E-Class Saloon E 200 CDI BlueEFFICIENCY.

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Model variant number	212005
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.143
Rated output (kW [PS] @ rpm) 1)	100 [136]/2800-4.600
Rated torque (Nm @ rpm) 1)	360/1.600 - 2.600
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	10,2
Top speed (km/h)	210

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	212005
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.143
Rated output (kW [PS] @ rpm) 1)	100 [136]/2800-4.600
Rated torque (Nm @ rpm) 1)	360/1.600 - 2.600
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	9,5
Top speed (km/h)	207

Power transmission (6-speed (manual))	
Drive system	Rear-wheel drive
Transmission	6-speed (manual)
Ratios	5,01/2,83/1,79/1,26/1,00/0,83/-/R1 4,57/R2 -
Final-drive ratio	2,470

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	6,5-6,3
Fuel consumption, extra-urban (l/100km) 2)	4,7-4,4
Fuel consumption, combined (l/100km) 2)	5,4-5,1
CO2 emissions combined (g/km) 2)	141-134
32259	A
Emissions category	Euro 5



## E-Class Saloon E 200 CDI BlueEFFICIENCY.

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	6,5-6,3
Fuel consumption, extra-urban (l/100km) 2)	4,7-4,4
Fuel consumption, combined (l/100km) 2)	5,4-5,1
CO2 emissions combined (g/km) 2)	141-134
32259	A
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	205/60 R 16
Tyres/wheels, rear	205/60 R 16
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	21/24/24

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.720/535
Perm. gross vehicle weight (kg)	2.255
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.900
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.471
Cd value	0,25
Track width, front (mm)	1.598
Track width, rear (mm)	1.614
Wheelbase (mm)	2.874

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.735/535
Perm. gross vehicle weight (kg)	2.270
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.900



## E-Class Saloon E 200 CDI BlueEFFICIENCY.

Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.471
Cd value	0,25
Track width, front (mm)	1.598
Track width, rear (mm)	1.614
Wheelbase (mm)	2.874

- 1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.
- 2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer
- 3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 220 CDI BlueEFFICIENCY (ECO Start-Stop-Funktion).

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Model variant number	212002
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.143
Rated output (kW [PS] @ rpm) 1)	125 [170]/3000-4.200
Rated torque (Nm @ rpm) 1)	400/1.400 - 2.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	8,7
Top speed (km/h)	228

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	212002
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.143
Rated output (kW [PS] @ rpm) 1)	125 [170]/3000-4.200
Rated torque (Nm @ rpm) 1)	400/1.400 - 2.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	8,4
Top speed (km/h)	227

Power transmission (6-speed (manual))	
Drive system	Rear-wheel drive
Transmission	6-speed (manual)
Ratios	5,01/2,83/1,79/1,26/1,00/0,83/-/R1 4,57/R2 -
Final-drive ratio	2,470

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	6,6-6,2
Fuel consumption, extra-urban (l/100km) 2)	4,6-4,2
Fuel consumption, combined (l/100km) 2)	5,3-5,0
CO2 emissions combined (g/km) 2)	139-130
32259	A
Emissions category	Euro 5



## E-Class Saloon E 220 CDI BlueEFFICIENCY (ECO Start-Stop-Funktion).

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	6,6-6,2
Fuel consumption, extra-urban (l/100km) 2)	4,5-4,2
Fuel consumption, combined (l/100km) 2)	5,3-4,9
CO2 emissions combined (g/km) 2)	138-129
32259	A
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	205/60 R 16
Tyres/wheels, rear	205/60 R 16
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	21/25/27

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.735/535
Perm. gross vehicle weight (kg)	2.270
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.900
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.471
Cd value	0,25
Track width, front (mm)	1.598
Track width, rear (mm)	1.614
Wheelbase (mm)	2.874

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.735/535
Perm. gross vehicle weight (kg)	2.270
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.000



## E-Class Saloon E 220 CDI BlueEFFICIENCY (ECO Start-Stop-Funktion ).

Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.471
Cd value	0,25
Track width, front (mm)	1.598
Track width, rear (mm)	1.614
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## E-Class Saloon E 250 CDI 4MATIC BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	212082
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.143
Rated output (kW [PS] @ rpm) 1)	150 [204]/4.200
Rated torque (Nm @ rpm) 1)	500/1.600 - 1.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	7,9
Top speed (km/h)	238

Power transmission (7G-TRONIC PLUS)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	7,1-7,0
Fuel consumption, extra-urban (l/100km) 2)	5,0-4,8
Fuel consumption, combined (l/100km) 2)	5,8-5,6
CO2 emissions combined (g/km) 2)	152-147
32259	B
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering	Rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	18/26/28

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.830/545
Perm. gross vehicle weight (kg)	2.375
Max. roof load (kg)	100



Mercedes-Benz

## E-Class Saloon E 250 CDI 4MATIC BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.474
Cd value	0,26
Track width, front (mm)	1.578
Track width, rear (mm)	1.594
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 250 CDI BlueEFFICIENCY.

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Model variant number	212003
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.143
Rated output (kW [PS] @ rpm) 1)	150 [204]/4.200
Rated torque (Nm @ rpm) 1)	500/1.600 - 1.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	7,7
Top speed (km/h)	240

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	212003
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.143
Rated output (kW [PS] @ rpm) 1)	150 [204]/4.200
Rated torque (Nm @ rpm) 1)	500/1.600 - 1.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	7,5
Top speed (km/h)	242

Power transmission (6-speed (manual))	
Drive system	Rear-wheel drive
Transmission	6-speed (manual)
Ratios	5,10/2,78/1,75/1,25/1,00/0,81/-/R1 4,62/R2 -
Final-drive ratio	2,650

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	6,6-6,2
Fuel consumption, extra-urban (l/100km) 2)	4,6-4,2
Fuel consumption, combined (l/100km) 2)	5,3-5,0
CO2 emissions combined (g/km) 2)	139-130
32259	A
Emissions category	Euro 5



## E-Class Saloon E 250 CDI BlueEFFICIENCY.

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	6,6-6,2
Fuel consumption, extra-urban (l/100km) 2)	4,5-4,2
Fuel consumption, combined (l/100km) 2)	5,3-4,9
CO2 emissions combined (g/km) 2)	138-129
32259	A
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	205/60 R 16
Tyres/wheels, rear	205/60 R 16
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	21/28/28

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.735/545
Perm. gross vehicle weight (kg)	2.280
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.900
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.471
Cd value	0,26
Track width, front (mm)	1.598
Track width, rear (mm)	1.614
Wheelbase (mm)	2.874

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.735/545
Perm. gross vehicle weight (kg)	2.280
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.000



## E-Class Saloon E 250 CDI BlueEFFICIENCY.

Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.471
Cd value	0,26
Track width, front (mm)	1.598
Track width, rear (mm)	1.614
Wheelbase (mm)	2.874

- 1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.
- 2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer
- 3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 350 BlueTEC.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	212024
Restriction code	0-802 Model year 2012
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.987
Rated output (kW [PS] @ rpm) 1)	155 [211]/3.400
Rated torque (Nm @ rpm) 1)	540/1.600 - 2.400
Compression ratio	16,5 : 1
Acceleration 0-100 km/h (s)	7,8
Top speed (km/h)	239

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	10,0-9,7
Fuel consumption, extra-urban (l/100km) 2)	5,6-5,2
Fuel consumption, combined (l/100km) 2)	7,2-6,8
CO <sub>2</sub> emissions combined (g/km) 2)	188-180
32259	C
Emissions category	Euro 6

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	225/55 R 16
Tyres/wheels, rear	225/55 R 16
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	21/28/28

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.845/525
Perm. gross vehicle weight (kg)	2.370
Max. roof load (kg)	100



## E-Class Saloon E 350 BlueTEC.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.472
Cd value	0,27
Track width, front (mm)	1.583
Track width, rear (mm)	1.599
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## E-Class Saloon E 300 CDI BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	212025
Restriction code	0-802 Model year 2012
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.987
Rated output (kW [PS] @ rpm) 1)	170 [231]/3.800
Rated torque (Nm @ rpm) 1)	540/1.600 - 2.400
Compression ratio	15,5 : 1
Acceleration 0-100 km/h (s)	6,8
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	9,4-8,9
Fuel consumption, extra-urban (l/100km) 2)	5,8-5,5
Fuel consumption, combined (l/100km) 2)	7,1-6,8
CO <sub>2</sub> emissions combined (g/km) 2)	186-179
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	225/55 R 16
Tyres/wheels, rear	225/55 R 16
Steering	electro-mechanical speed-sensitive rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	21/28/28

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.825/525
Perm. gross vehicle weight (kg)	2.350
Max. roof load (kg)	100



## E-Class Saloon E 300 CDI BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.465
Cd value	0,27
Track width, front (mm)	1.585
Track width, rear (mm)	1.604
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 350 CDI 4MATIC BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	212093
Restriction code	0-802 Model year 2012
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.987
Rated output (kW [PS] @ rpm) 1)	195 [265]/3.800
Rated torque (Nm @ rpm) 1)	620/1.600 - 2.400
Compression ratio	15,5 : 1
Acceleration 0-100 km/h (s)	6,7
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	8,3-8,2
Fuel consumption, extra-urban (l/100km) 2)	5,6-5,5
Fuel consumption, combined (l/100km) 2)	6,7-6,6
CO2 emissions combined (g/km) 2)	175-173
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	18/28/28

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.900/545
Perm. gross vehicle weight (kg)	2.445
Max. roof load (kg)	100



Mercedes-Benz

## E-Class Saloon E 350 CDI 4MATIC BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.474
Cd value	0,28
Track width, front (mm)	1.578
Track width, rear (mm)	1.594
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 350 CDI BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	212023
Restriction code	0-802 Model year 2012
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.987
Rated output (kW [PS] @ rpm) 1)	195 [265]/3.800
Rated torque (Nm @ rpm) 1)	620/1.600 - 2.400
Compression ratio	15,5 : 1
Acceleration 0-100 km/h (s)	6,2
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	8,3-7,7
Fuel consumption, extra-urban (l/100km) 2)	5,4-5,0
Fuel consumption, combined (l/100km) 2)	6,4-6,0
CO <sub>2</sub> emissions combined (g/km) 2)	168-159
32259	B
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	225/55 R 16
Tyres/wheels, rear	225/55 R 16
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	21/28/28

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.835/545
Perm. gross vehicle weight (kg)	2.380
Max. roof load (kg)	100



Mercedes-Benz

## E-Class Saloon E 350 CDI BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.472
Cd value	0,27
Track width, front (mm)	1.583
Track width, rear (mm)	1.599
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## E-Class Saloon E 200 NGT BlueEFFICIENCY.

Engine and performance (5-speed automatic with Touchshift)	
Arrangement/no. of cylinders	L4
Model variant number	212041
Restriction code	0-802 Model year 2012
Market launch	2011.09
Displacement (cm <sup>3</sup> )	1.796
Rated output (kW [PS] @ rpm) 1)	120 [163]/5.500
Rated torque (Nm @ rpm) 1)	240/3.000 - 4.000
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	10,4
Top speed (km/h)	224

Power transmission (5-speed automatic with Touchshift)	
Drive system	Rear-wheel drive
Transmission	5-speed automatic with Touchshift
Ratios	3,95/2,42/1,49/1,00/0,83/-/-/R1 3,15/R2 1,93
Final-drive ratio	3,270

Fuel and emissions (5-speed automatic with Touchshift)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	11,8-11,5
Fuel consumption, extra-urban (l/100km) 2)	6,6-6,1
Fuel consumption, combined (l/100km) 2)	8,5-8,1
CO2 emissions combined (g/km) 2)	198-190
32259	D
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	225/55 R 16
Tyres/wheels, rear	225/55 R 16
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	19/24/20



## E-Class Saloon E 200 NGT BlueEFFICIENCY.

Quantities, dimensions and weights (5-speed automatic with Touchshift)	
Kerb weight/payload (kg) 3)	1.735/505
Perm. gross vehicle weight (kg)	2.240
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.900
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.472
Cd value	0,26
Track width, front (mm)	1.583
Track width, rear (mm)	1.599
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 200 BlueEFFICIENCY.

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Model variant number	212048
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	1.796
Rated output (kW [PS] @ rpm) 1)	135 [184]/5.250
Rated torque (Nm @ rpm) 1)	270/1.800 - 4.600
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	8,5
Top speed (km/h)	232

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	212048
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	1.796
Rated output (kW [PS] @ rpm) 1)	135 [184]/5.250
Rated torque (Nm @ rpm) 1)	270/1.800 - 4.600
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	7,9
Top speed (km/h)	232

Power transmission (6-speed (manual))	
Drive system	Rear-wheel drive
Transmission	6-speed (manual)
Ratios	4,99/2,82/1,78/1,25/1,00/0,82/-/R1 4,54/R2 -
Final-drive ratio	3,070

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,070

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	10,0-9,8
Fuel consumption, extra-urban (l/100km) 2)	5,9-5,6
Fuel consumption, combined (l/100km) 2)	7,4-7,1
CO2 emissions combined (g/km) 2)	172-165
32259	D
Emissions category	Euro 5



## E-Class Saloon E 200 BlueEFFICIENCY.

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	9,1-8,8
Fuel consumption, extra-urban (l/100km) 2)	5,6-5,2
Fuel consumption, combined (l/100km) 2)	6,9-6,5
CO2 emissions combined (g/km) 2)	160-152
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	205/60 R 16
Tyres/wheels, rear	205/60 R 16
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	19/24/20

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.615/535
Perm. gross vehicle weight (kg)	2.150
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.700
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.471
Cd value	0,26
Track width, front (mm)	1.598
Track width, rear (mm)	1.614
Wheelbase (mm)	2.874

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.615/535
Perm. gross vehicle weight (kg)	2.150
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.900



## E-Class Saloon E 200 BlueEFFICIENCY.

Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.471
Cd value	0,26
Track width, front (mm)	1.598
Track width, rear (mm)	1.614
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 250 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	212047
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	1.796
Rated output (kW [PS] @ rpm) 1)	150 [204]/5.500
Rated torque (Nm @ rpm) 1)	310/2.000 - 4.300
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	7,7
Top speed (km/h)	240

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,070

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	9,2-8,9
Fuel consumption, extra-urban (l/100km) 2)	5,7-5,3
Fuel consumption, combined (l/100km) 2)	7,0-6,6
CO2 emissions combined (g/km) 2)	162-154
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	225/55 R 16
Tyres/wheels, rear	225/55 R 16
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	19/24/20



## E-Class Saloon E 250 BlueEFFICIENCY.

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.650/535
Perm. gross vehicle weight (kg)	2.185
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.900
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.472
Cd value	0,26
Track width, front (mm)	1.583
Track width, rear (mm)	1.599
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## E-Class Saloon E 300 4MATIC BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	212080
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	3.498
Rated output (kW [PS] @ rpm) 1)	185 [252]/6.500
Rated torque (Nm @ rpm) 1)	340/3.500 - 4.500
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	7,4
Top speed (km/h)	245

Power transmission (7G-TRONIC PLUS)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,070

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	9,9-9,9
Fuel consumption, extra-urban (l/100km) 2)	6,0-5,9
Fuel consumption, combined (l/100km) 2)	7,5-7,4
CO2 emissions combined (g/km) 2)	176-174
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.



## E-Class Saloon E 300 4MATIC BlueEFFICIENCY.

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.815/545
Perm. gross vehicle weight (kg)	2.360
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.474
Cd value	0,26
Track width, front (mm)	1.578
Track width, rear (mm)	1.594
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 300 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	212055
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	3.498
Rated output (kW [PS] @ rpm) 1)	185 [252]/6.500
Rated torque (Nm @ rpm) 1)	340/3.500 - 4.500
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	7,1
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	k. A.

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	9,5-9,5
Fuel consumption, extra-urban (l/100km) 2)	5,6-5,3
Fuel consumption, combined (l/100km) 2)	7,0-6,8
CO2 emissions combined (g/km) 2)	164-159
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	225/55 R 16
Tyres/wheels, rear	225/55 R 16
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.



## E-Class Saloon E 300 BlueEFFICIENCY.

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.730/545
Perm. gross vehicle weight (kg)	2.275
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.472
Cd value	0,26
Track width, front (mm)	1.583
Track width, rear (mm)	1.599
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## E-Class Saloon E 350 4MATIC BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	212088
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	3.498
Rated output (kW [PS] @ rpm) 1)	225 [306]/6.500
Rated torque (Nm @ rpm) 1)	370/3.500 - 5.250
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	6,6
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,070

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	9,9-9,9
Fuel consumption, extra-urban (l/100km) 2)	6,0-5,9
Fuel consumption, combined (l/100km) 2)	7,5-7,4
CO2 emissions combined (g/km) 2)	176-174
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.



## E-Class Saloon E 350 4MATIC BlueEFFICIENCY.

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.825/545
Perm. gross vehicle weight (kg)	2.370
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.474
Cd value	0,27
Track width, front (mm)	1.578
Track width, rear (mm)	1.594
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## E-Class Saloon E 350 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	212059
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	3.498
Rated output (kW [PS] @ rpm) 1)	225 [306]/6.500
Rated torque (Nm @ rpm) 1)	370/3.500 - 5.250
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	6,3
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,066

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	9,5-9,5
Fuel consumption, extra-urban (l/100km) 2)	5,6-5,3
Fuel consumption, combined (l/100km) 2)	7,0-6,8
CO2 emissions combined (g/km) 2)	164-159
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	225/55 R 16
Tyres/wheels, rear	225/55 R 16
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	21/28/22



## E-Class Saloon E 350 BlueEFFICIENCY.

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.735/545
Perm. gross vehicle weight (kg)	2.280
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.472
Cd value	0,26
Track width, front (mm)	1.583
Track width, rear (mm)	1.599
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## E-Class Saloon E 500 4MATIC BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V8
Model variant number	212091
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	4.663
Rated output (kW [PS] @ rpm) 1)	300 [408]/5000-5.750
Rated torque (Nm @ rpm) 1)	600/1.600 - 4.750
Compression ratio	10,5 : 1
Acceleration 0-100 km/h (s)	5,2
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,473

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	13,0-13,0
Fuel consumption, extra-urban (l/100km) 2)	7,2-7,2
Fuel consumption, combined (l/100km) 2)	9,4-9,4
CO2 emissions combined (g/km) 2)	219-219
32259	E
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Damper with damper valve/Air spring, Damper with damper valve
Tyres/wheels, front	245/40 R 18
Tyres/wheels, rear	245/40 R 18
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.



## E-Class Saloon E 500 4MATIC BlueEFFICIENCY.

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.985/525
Perm. gross vehicle weight (kg)	2.510
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.458
Cd value	0,28
Track width, front (mm)	1.580
Track width, rear (mm)	1.600
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 500 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V8
Model variant number	212073
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	4.663
Rated output (kW [PS] @ rpm) 1)	300 [408]/5000-5.750
Rated torque (Nm @ rpm) 1)	600/1.600 - 4.750
Compression ratio	10,5 : 1
Acceleration 0-100 km/h (s)	5,2
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,473

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	12,6-12,6
Fuel consumption, extra-urban (l/100km) 2)	6,7-6,7
Fuel consumption, combined (l/100km) 2)	8,9-8,9
CO2 emissions combined (g/km) 2)	209-209
32259	E
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Damper with damper valve/Air spring, Damper with damper valve
Tyres/wheels, front	245/40 R 18
Tyres/wheels, rear	245/40 R 18
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.940/545
Perm. gross vehicle weight (kg)	2.485
Max. roof load (kg)	100



## E-Class Saloon E 500 BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/2.100
Permissible drawbar load (kg)	84
Turning circle (m)	11,25
Vehicle length (mm)	4.868
Vehicle width (mm)	1.854
Vehicle height at kerb weight (mm)	1.454
Cd value	0,28
Track width, front (mm)	1.580
Track width, rear (mm)	1.588
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 63 AMG.

Engine and performance (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Arrangement/no. of cylinders	V8
Model variant number	212074
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	5.461
Rated output (kW [PS] @ rpm) 1)	386 [525]/k. A.
Rated torque (Nm @ rpm) 1)	700/n.a.
Compression ratio	10,0 : 1
Acceleration 0-100 km/h (s)	4,3
Top speed (km/h)	250

Power transmission (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Drive system	Rear-wheel drive
Transmission	AMG SPEEDSHIFT MCT 7-speed sports transmission
Ratios	k. A./k. A./k. A./k. A./k. A./k. A./k. A./R1 k. A./R2 k. A.
Final-drive ratio	2,65

Fuel and emissions (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Tank capacity/reserve (l)	66/14
Fuel consumption, urban (l/100km) 2)	13,8-13,8
Fuel consumption, extra-urban (l/100km) 2)	7,5-7,5
Fuel consumption, combined (l/100km) 2)	9,8-9,8
CO2 emissions combined (g/km) 2)	230-230
32259	F
Emissions category	Euro 5

Chassis and steering	
Front axle	no details
Rear axle	no details
Springs, front/rear	Spring strut with coil spring, no details/Air spring, no details
Tyres/wheels, front	255/40 ZR 18 (99Y) XL
Tyres/wheels, rear	285/35 ZR 18 (101Y) XL
Steering	hydraulic speed-sensitive rack-and-pinion steering with constant sports ratio
Front brakes	Compound brake discs, internally ventilated and perforated/discs, internally ventilated and perforated
Rear brakes	one-piece, externally ventilated and perforated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.



## E-Class Saloon E 63 AMG.

Quantities, dimensions and weights (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Kerb weight/payload (kg) 3)	1.840/550
Perm. gross vehicle weight (kg)	2.390
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	11,3
Vehicle length (mm)	4.883
Vehicle width (mm)	1.872
Vehicle height at kerb weight (mm)	1.440
Cd value	0,29
Track width, front (mm)	1.625
Track width, rear (mm)	1.594
Wheelbase (mm)	k. A.

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## E-Class Saloon E 63 AMG (Performance Package).

Engine and performance (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Arrangement/no. of cylinders	V8
Model variant number	212074
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function, 0-P30 - Performance package
Market launch	2011.09
Displacement (cm <sup>3</sup> )	5,461
Rated output (kW [PS] @ rpm) 1)	410 [557]/k. A.
Rated torque (Nm @ rpm) 1)	800/n.a.
Compression ratio	10,0 : 1
Acceleration 0-100 km/h (s)	4,2
Top speed (km/h)	250

Power transmission (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Drive system	Rear-wheel drive
Transmission	AMG SPEEDSHIFT MCT 7-speed sports transmission
Ratios	k. A./k. A./k. A./k. A./k. A./k. A./k. A./R1 k. A./R2 k. A.
Final-drive ratio	2,65

Fuel and emissions (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Tank capacity/reserve (l)	66/14
Fuel consumption, urban (l/100km) 2)	13,8-13,8
Fuel consumption, extra-urban (l/100km) 2)	7,5-7,5
Fuel consumption, combined (l/100km) 2)	9,8-9,8
CO2 emissions combined (g/km) 2)	230-230
32259	F
Emissions category	Euro 5

Chassis and steering	
Front axle	no details
Rear axle	no details
Springs, front/rear	Spring strut with coil spring, no details/Air spring, no details
Tyres/wheels, front	255/40 ZR 18 (99Y) XL
Tyres/wheels, rear	285/35 ZR 18 (101Y) XL
Steering	hydraulic speed-sensitive rack-and-pinion steering with constant sports ratio
Front brakes	Compound discs, internally ventilated and perforated
Rear brakes	one-piece, externally ventilated and perforated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.



## E-Class Saloon E 63 AMG (Performance Package).

Quantities, dimensions and weights (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Kerb weight/payload (kg) 3)	1.840/550
Perm. gross vehicle weight (kg)	2.390
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	11,3
Vehicle length (mm)	4.883
Vehicle width (mm)	1.872
Vehicle height at kerb weight (mm)	1.440
Cd value	0,29
Track width, front (mm)	1.625
Track width, rear (mm)	1.594
Wheelbase (mm)	k. A.

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly