



E-Class Coupé E 220 CDI BlueEFFICIENCY.

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Model variant number	207302
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	2.143
Rated output (kW [PS] @ rpm) 1)	125 [170]/3000-4.200
Rated torque (Nm @ rpm) 1)	400/1.400 - 2.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	8,5
Top speed (km/h)	235

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	207302
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	2.143
Rated output (kW [PS] @ rpm) 1)	125 [170]/3000-4.200
Rated torque (Nm @ rpm) 1)	400/1.400 - 2.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	8,3
Top speed (km/h)	234

Power transmission (6-speed (manual))	
Drive system	Rear-wheel drive
Transmission	6-speed (manual)
Ratios	5,01/2,83/1,79/1,26/1,00/0,83/-/R1 4,57/R2 -
Final-drive ratio	2,240

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	6,1-5,9
Fuel consumption, extra-urban (l/100km) 2)	4,4-4,0
Fuel consumption, combined (l/100km) 2)	5,0-4,7
CO2 emissions combined (g/km) 2)	131-123
32259	A
Emissions category	Euro 5



E-Class Coupé E 220 CDI BlueEFFICIENCY.

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	6,6-6,4
Fuel consumption, extra-urban (l/100km) 2)	4,5-4,0
Fuel consumption, combined (l/100km) 2)	5,3-4,9
CO2 emissions combined (g/km) 2)	138-128
32259	A
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	235/45 R 17
Tyres/wheels, rear	235/45 R 17
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	19/26/25

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.670/470
Perm. gross vehicle weight (kg)	2.140
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75
Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.393
Cd value	0,24
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.680/470
Perm. gross vehicle weight (kg)	2.150
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75



E-Class Coupé E 220 CDI BlueEFFICIENCY.

Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.393
Cd value	0,24
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



E-Class Coupé E 250 CDI BlueEFFICIENCY.

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Model variant number	207303
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	2.143
Rated output (kW [PS] @ rpm) 1)	150 [204]/4.200
Rated torque (Nm @ rpm) 1)	500/1.600 - 1.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	7,4
Top speed (km/h)	250

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	207303
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	2.143
Rated output (kW [PS] @ rpm) 1)	150 [204]/4.200
Rated torque (Nm @ rpm) 1)	500/1.600 - 1.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	7,3
Top speed (km/h)	247

Power transmission (6-speed (manual))	
Drive system	Rear-wheel drive
Transmission	6-speed (manual)
Ratios	5,10/2,78/1,75/1,25/1,00/0,81/-/R1 4,62/R2 -
Final-drive ratio	2,470

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	6,7-6,3
Fuel consumption, extra-urban (l/100km) 2)	4,4-4,0
Fuel consumption, combined (l/100km) 2)	5,3-4,9
CO2 emissions combined (g/km) 2)	138-128
32259	A
Emissions category	Euro 5



E-Class Coupé E 250 CDI BlueEFFICIENCY.

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	6,6-6,4
Fuel consumption, extra-urban (l/100km) 2)	4,5-4,0
Fuel consumption, combined (l/100km) 2)	5,3-4,9
CO2 emissions combined (g/km) 2)	138-128
32259	A
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	235/45 R 17
Tyres/wheels, rear	235/45 R 17
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	19/26/25

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.700/470
Perm. gross vehicle weight (kg)	2.170
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75
Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.397
Cd value	0,24
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.700/470
Perm. gross vehicle weight (kg)	2.170
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75



E-Class Coupé E 250 CDI BlueEFFICIENCY.

Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.397
Cd value	0,24
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

- 1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.
- 2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer
- 3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



E-Class Coupé E 350 CDI BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	207323
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	2.987
Rated output (kW [PS] @ rpm) 1)	195 [265]/3.800
Rated torque (Nm @ rpm) 1)	620/1.600 - 2.400
Compression ratio	15,5 : 1
Acceleration 0-100 km/h (s)	6,1
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,470

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	7,5-7,3
Fuel consumption, extra-urban (l/100km) 2)	5,2-4,9
Fuel consumption, combined (l/100km) 2)	6,1-6,0
CO2 emissions combined (g/km) 2)	157-154
32259	B
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	235/45 R 17
Tyres/wheels, rear	235/45 R 17
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	19/26/25

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.735/470
Perm. gross vehicle weight (kg)	2.205
Max. roof load (kg)	100



Mercedes-Benz

E-Class Coupé E 350 CDI BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75
Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.397
Cd value	0,27
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



E-Class Coupé E 200 CGI BlueEFFICIENCY (ECO Start-Stop).

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Model variant number	207348
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	1.796
Rated output (kW [PS] @ rpm) 1)	135 [184]/5.250
Rated torque (Nm @ rpm) 1)	270/1.800 - 4.600
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	8,5
Top speed (km/h)	240

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	207348
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	1.796
Rated output (kW [PS] @ rpm) 1)	135 [184]/5.250
Rated torque (Nm @ rpm) 1)	270/1.800 - 4.600
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	7,8
Top speed (km/h)	237

Power transmission (6-speed (manual))	
Drive system	Rear-wheel drive
Transmission	6-speed (manual)
Ratios	4,99/2,82/1,78/1,25/1,00/0,82/-/R1 4,54/R2 -
Final-drive ratio	2,870

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,070

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	9,7-9,7
Fuel consumption, extra-urban (l/100km) 2)	5,8-5,3
Fuel consumption, combined (l/100km) 2)	7,2-6,9
CO2 emissions combined (g/km) 2)	167-160
32259	D
Emissions category	Euro 5



E-Class Coupé E 200 CGI BlueEFFICIENCY (ECO Start-Stop).

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	9,1-8,6
Fuel consumption, extra-urban (l/100km) 2)	5,7-5,2
Fuel consumption, combined (l/100km) 2)	6,9-6,4
CO2 emissions combined (g/km) 2)	161-149
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	235/45 R 17
Tyres/wheels, rear	235/45 R 17
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	16/24/23

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.560/470
Perm. gross vehicle weight (kg)	2.030
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75
Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.393
Cd value	0,24
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.585/470
Perm. gross vehicle weight (kg)	2.055
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75



Mercedes-Benz

E-Class Coupé E 200 CGI BlueEFFICIENCY (ECO Start-Stop).

Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.393
Cd value	0,24
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



E-Class Coupé E 250 CGI BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	207347
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	1.796
Rated output (kW [PS] @ rpm) 1)	150 [204]/5.500
Rated torque (Nm @ rpm) 1)	310/2.300 - 4.300
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	7,4
Top speed (km/h)	247

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,070

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	9,1-8,6
Fuel consumption, extra-urban (l/100km) 2)	5,7-5,2
Fuel consumption, combined (l/100km) 2)	6,9-6,4
CO ₂ emissions combined (g/km) 2)	161-149
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	235/45 R 17
Tyres/wheels, rear	235/45 R 17
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	16/24/23

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.600/470
Perm. gross vehicle weight (kg)	2.070
Max. roof load (kg)	100



Mercedes-Benz

E-Class Coupé E 250 CGI BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75
Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.397
Cd value	0,24
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



E-Class Coupé E 300 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	207355
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	3.498
Rated output (kW [PS] @ rpm) 1)	185 [252]/6.500
Rated torque (Nm @ rpm) 1)	340/3.500 - 4.500
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	6,9
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,820

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	9,8-9,7
Fuel consumption, extra-urban (l/100km) 2)	5,6-5,4
Fuel consumption, combined (l/100km) 2)	7,2-7,0
CO ₂ emissions combined (g/km) 2)	167-164
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	235/45 R 17
Tyres/wheels, rear	235/45 R 17
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	19/25/25

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.660/470
Perm. gross vehicle weight (kg)	2.130
Max. roof load (kg)	100



Mercedes-Benz

E-Class Coupé E 300 BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75
Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.397
Cd value	0,26
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



E-Class Coupé E 350 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	207359
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.06
Displacement (cm ³)	3.498
Rated output (kW [PS] @ rpm) 1)	225 [306]/6.500
Rated torque (Nm @ rpm) 1)	370/3.500 - 5.250
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	6,2
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,820

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	9,8-9,7
Fuel consumption, extra-urban (l/100km) 2)	5,6-5,4
Fuel consumption, combined (l/100km) 2)	7,2-7,0
CO ₂ emissions combined (g/km) 2)	167-164
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	235/45 R 17
Tyres/wheels, rear	235/45 R 17
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	19/25/25

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.660/470
Perm. gross vehicle weight (kg)	2.130
Max. roof load (kg)	100



Mercedes-Benz

E-Class Coupé E 350 BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	750/1.800
Permissible drawbar load (kg)	75
Turning circle (m)	10,95
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.397
Cd value	0,26
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



E-Class Coupé E 500 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V8
Model variant number	207373
Restriction code	0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm ³)	4.663
Rated output (kW [PS] @ rpm) 1)	300 [408]/5000-5.750
Rated torque (Nm @ rpm) 1)	600/1.600 - 4.750
Compression ratio	10,5 : 1
Acceleration 0-100 km/h (s)	5,1
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,650

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	66/8,0
Fuel consumption, urban (l/100km) 2)	12,7-12,7
Fuel consumption, extra-urban (l/100km) 2)	6,8-6,8
Fuel consumption, combined (l/100km) 2)	8,9-8,9
CO ₂ emissions combined (g/km) 2)	209-209
32259	E
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Damper with damper valve/Coil spring, Damper with damper valve
Tyres/wheels, front	235/40 R 18
Tyres/wheels, rear	255/35 R 18
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	19/27/29

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.795/455
Perm. gross vehicle weight (kg)	2.250
Max. roof load (kg)	100



E-Class Coupé E 500 BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	k. A./k. A.
Permissible drawbar load (kg)	k. A.
Turning circle (m)	11,20
Vehicle length (mm)	4.698
Vehicle width (mm)	1.786
Vehicle height at kerb weight (mm)	1.398
Cd value	0,28
Track width, front (mm)	1.538
Track width, rear (mm)	1.544
Wheelbase (mm)	2.760

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly