



S-Class Saloon S 250 CDI BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Displacement (cm ³)	2.143
Rated output (35) 1)	150 /4.200
Rated torque (Nm @ rpm) 1)	500/1.600 - 1.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	8,2
Top speed (km/h)	240

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,82

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	83/11
Fuel consumption, urban (l/100km) 2)	7,0-7,1
Fuel consumption, extra-urban (l/100km) 2)	5,0-5,0
Fuel consumption, combined (l/100km) 2)	5,7-5,8
CO ₂ emissions combined (g/km) 2)	149-151
Cd value	0,26
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Single tube gas pressure/Air spring, Single tube gas pressure
Tyres/wheels, front	235/55 R 17 99 W
Tyres/wheels, rear	235/55 R 17 99 W
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, solid

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.970/595
Perm. gross vehicle weight (kg)	2.565
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,80
perm. trailer load, braked/unbraked (kg)	k. A. /k. A.

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently



Mercedes-Benz

S-Class Saloon S 250 CDI BlueEFFICIENCY.

applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



S-Class Saloon S 350 BlueTEC.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Displacement (cm ³)	2.987
Rated output (35) 1)	190 /3.600
Rated torque (Nm @ rpm) 1)	620/1.600 - 2.400
Compression ratio	15,5 : 1
Acceleration 0-100 km/h (s)	7,1
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,47

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	83/11
Fuel consumption, urban (l/100km) 2)	7,7-7,9
Fuel consumption, extra-urban (l/100km) 2)	5,4-5,6
Fuel consumption, combined (l/100km) 2)	6,2-6,4
CO2 emissions combined (g/km) 2)	164-168
Cd value	0,26
Emissions category	Euro 6

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Single tube gas pressure/Air spring, Single tube gas pressure
Tyres/wheels, front	235/55 R 17 99 W
Tyres/wheels, rear	235/55 R 17 99 W
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.995/595
Perm. gross vehicle weight (kg)	2.590
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,80
perm. trailer load, braked/unbraked (kg)	750/2.100

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

S-Class Saloon S 350 BlueTEC.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



S-Class Saloon S 350 BlueTEC 4MATIC.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Displacement (cm ³)	2.987
Rated output (35) 1)	190 /3.600
Rated torque (Nm @ rpm) 1)	620/1.600 - 2.400
Compression ratio	15,5 : 1
Acceleration 0-100 km/h (s)	7,1
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,65

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	83/11
Fuel consumption, urban (l/100km) 2)	9,9-10,1
Fuel consumption, extra-urban (l/100km) 2)	5,8-5,9
Fuel consumption, combined (l/100km) 2)	7,3-7,4
CO2 emissions combined (g/km) 2)	193-195
Cd value	0,27
Emissions category	Euro 6

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Single tube gas pressure/Air spring, Single tube gas pressure
Tyres/wheels, front	235/55 R 17 99 W
Tyres/wheels, rear	235/55 R 17 99 W
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	2.065/595
Perm. gross vehicle weight (kg)	2.660
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,80
perm. trailer load, braked/unbraked (kg)	750/2.100

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

S-Class Saloon S 350 BlueTEC 4MATIC.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



S-Class Saloon S 400 HYBRID.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	V6
Displacement (cm ³)	3.498
Rated output (35) 1)	205 /6.000
Rated torque (Nm @ rpm) 1)	350/3.000 - 5.500
Compression ratio	11,7 : 1
Acceleration 0-100 km/h (s)	7,2
Top speed (km/h)	250

Power transmission (7G-TRONIC)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,07

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	90/11
Fuel consumption, urban (l/100km) 2)	10,7-10,9
Fuel consumption, extra-urban (l/100km) 2)	6,3-6,5
Fuel consumption, combined (l/100km) 2)	7,9-8,1
CO2 emissions combined (g/km) 2)	186-189
Cd value	0,27
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Single tube gas pressure/Air spring, Single tube gas pressure
Tyres/wheels, front	235/55 R 17 99 W
Tyres/wheels, rear	235/55 R 17 99 W
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, solid

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	1.955/595
Perm. gross vehicle weight (kg)	2.550
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,80
perm. trailer load, braked/unbraked (kg)	-/-

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

S-Class Saloon S 400 HYBRID.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



S-Class Saloon S 350 4MATIC BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Displacement (cm ³)	3.498
Rated output (35) 1)	225 /6.500
Rated torque (Nm @ rpm) 1)	370/3.500 - 5.250
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	6,9
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,07

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	83/11
Fuel consumption, urban (l/100km) 2)	10,8-10,9
Fuel consumption, extra-urban (l/100km) 2)	6,5-6,7
Fuel consumption, combined (l/100km) 2)	8,1-8,3
CO2 emissions combined (g/km) 2)	189-193
Cd value	0,28
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Single tube gas pressure/Air spring, Single tube gas pressure
Tyres/wheels, front	235/55 R 17 99 W
Tyres/wheels, rear	235/55 R 17 99 W
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.980/600
Perm. gross vehicle weight (kg)	2.580
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,80
perm. trailer load, braked/unbraked (kg)	750/2.100

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

S-Class Saloon S 350 4MATIC BlueEFFICIENCY.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



S-Class Saloon S 350 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Displacement (cm ³)	3.498
Rated output (35) 1)	225 /6.500
Rated torque (Nm @ rpm) 1)	370/3.500 - 5.250
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	6,9
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,07

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	83/11
Fuel consumption, urban (l/100km) 2)	10,2-10,6
Fuel consumption, extra-urban (l/100km) 2)	6,0-6,3
Fuel consumption, combined (l/100km) 2)	7,6-7,9
CO2 emissions combined (g/km) 2)	177-184
Cd value	0,27
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Single tube gas pressure/Air spring, Single tube gas pressure
Tyres/wheels, front	235/55 R 17 99 W
Tyres/wheels, rear	235/55 R 17 99 W
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.910/595
Perm. gross vehicle weight (kg)	2.505
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,80
perm. trailer load, braked/unbraked (kg)	750/2.100

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

S-Class Saloon S 350 BlueEFFICIENCY.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

S-Class Saloon S 500 4MATIC BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V8
Displacement (cm ³)	4.663
Rated output (35) 1)	320 /5.250
Rated torque (Nm @ rpm) 1)	700/1.800 - 3.500
Compression ratio	10,5 : 1
Acceleration 0-100 km/h (s)	5,0
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,65

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	83/11
Fuel consumption, urban (l/100km) 2)	13,8-13,8
Fuel consumption, extra-urban (l/100km) 2)	7,5-7,6
Fuel consumption, combined (l/100km) 2)	9,8-9,8
CO ₂ emissions combined (g/km) 2)	228-229
Cd value	0,28
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Single tube gas pressure/Air spring, Single tube gas pressure
Tyres/wheels, front	255/45 R 18 99 Y
Tyres/wheels, rear	255/45 R 18 99 Y
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	2.075/610
Perm. gross vehicle weight (kg)	2.685
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,80
perm. trailer load, braked/unbraked (kg)	750/2.100

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

S-Class Saloon S 500 4MATIC BlueEFFICIENCY.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

S-Class Saloon S 500 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V8
Displacement (cm ³)	4.663
Rated output (35) 1)	320 /5.250
Rated torque (Nm @ rpm) 1)	700/1.800 - 3.500
Compression ratio	10,5 : 1
Acceleration 0-100 km/h (s)	5,0
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,65

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	83/11
Fuel consumption, urban (l/100km) 2)	12,9-13,4
Fuel consumption, extra-urban (l/100km) 2)	7,3-7,4
Fuel consumption, combined (l/100km) 2)	9,4-9,6
CO ₂ emissions combined (g/km) 2)	219-224
Cd value	0,27
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Single tube gas pressure/Air spring, Single tube gas pressure
Tyres/wheels, front	255/45 R 18 99 Y
Tyres/wheels, rear	255/45 R 18 99 Y
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	2.010/605
Perm. gross vehicle weight (kg)	2.615
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,80
perm. trailer load, braked/unbraked (kg)	750/2.100

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

S-Class Saloon S 500 BlueEFFICIENCY.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



S-Class Saloon S 63 AMG.

Engine and performance (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Arrangement/no. of cylinders	V8
Displacement (cm ³)	5.461
Rated output (35) 1)	400 /5250 - 5.750
Rated torque (Nm @ rpm) 1)	800/2.000 - 4.500
Compression ratio	10,0 : 1
Acceleration 0-100 km/h (s)	4,5
Top speed (km/h)	250

Power transmission (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Drive system	Rear-wheel drive
Transmission	AMG SPEEDSHIFT MCT 7-speed sports transmission
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 k. A.
Final-drive ratio	2,65

Fuel and emissions (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Tank capacity/reserve (l)	90/14
Fuel consumption, urban (l/100km) 2)	14,4-14,4
Fuel consumption, extra-urban (l/100km) 2)	8,2-8,2
Fuel consumption, combined (l/100km) 2)	10,5-10,5
CO2 emissions combined (g/km) 2)	244-244
Cd value	k. A.
Emissions category	Euro 5

Chassis and steering	
Front axle	no details
Rear axle	no details
Springs, front/rear	no details, no details/no details, no details
Tyres/wheels, front	255/40 ZR 19 Extra Load
Tyres/wheels, rear	275/40 ZR 19 Extra Load
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Double sliding callipers with compound brake discs
Rear brakes	Sliding frame-type callipers with compound brake discs

Quantities, dimensions and weights (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Kerb weight/payload (kg) 3)	2.120/550
Perm. gross vehicle weight (kg)	2.670
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,82
perm. trailer load, braked/unbraked (kg)	-/-

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer



Mercedes-Benz

S-Class Saloon S 63 AMG.

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



S-Class Saloon S 63 AMG (Performance Package).

Engine and performance (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Arrangement/no. of cylinders	V8
Displacement (cm ³)	5.461
Rated output (35) 1)	420 /5.500
Rated torque (Nm @ rpm) 1)	900/2.250 - 3.750
Compression ratio	10,0 : 1
Acceleration 0-100 km/h (s)	4,4
Top speed (km/h)	300

Power transmission (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Drive system	Rear-wheel drive
Transmission	AMG SPEEDSHIFT MCT 7-speed sports transmission
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 k. A.
Final-drive ratio	2,65

Fuel and emissions (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Tank capacity/reserve (l)	90/14
Fuel consumption, urban (l/100km) 2)	14,4-14,4
Fuel consumption, extra-urban (l/100km) 2)	8,2-8,2
Fuel consumption, combined (l/100km) 2)	10,5-10,5
CO2 emissions combined (g/km) 2)	244-244
Cd value	k. A.
Emissions category	Euro 5

Chassis and steering	
Front axle	no details
Rear axle	no details
Springs, front/rear	no details, no details/no details, no details
Tyres/wheels, front	255/40 ZR 19 Extra Load
Tyres/wheels, rear	275/40 ZR 19 Extra Load
Steering	hydraulic speed-sensitive rack-and-pinion steering
Front brakes	Double sliding callipers with compound brake discs
Rear brakes	Sliding frame-type callipers with compound brake discs

Quantities, dimensions and weights (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Kerb weight/payload (kg) 3)	2.120/550
Perm. gross vehicle weight (kg)	2.670
Max. roof load (kg)	100
Boot capacity (VDA) (l)	560
Turning circle (m)	11,82
perm. trailer load, braked/unbraked (kg)	-/-

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer



Mercedes-Benz

S-Class Saloon S 63 AMG (Performance Package).

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly