



SL-Class Roadster SL 300.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	V6
Displacement (cm ³)	2.996
Rated output (35) 1)	170 /6.000
Rated torque (Nm @ rpm) 1)	300/2.500 - 5.000
Compression ratio	11,1 : 1
Acceleration 0-100 km/h (s)	7,8
Top speed (km/h)	250

Power transmission (7G-TRONIC)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,07

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	80/10
Fuel consumption, urban (l/100km) 2)	13,5-13,5
Fuel consumption, extra-urban (l/100km) 2)	6,8-6,8
Fuel consumption, combined (l/100km) 2)	9,3-9,3
CO2 emissions combined (g/km) 2)	217-217
Cd value	0,30
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Single tube gas pressure/Coil spring, Single tube gas pressure
Tyres/wheels, front	255/45 R 17
Tyres/wheels, rear	255/45 R 17
Steering	hydraulic rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	1.815/295
Perm. gross vehicle weight (kg)	2.110
Max. roof load (kg)	75
Boot capacity (VDA) (l)	235-339
Turning circle (m)	11,04
perm. trailer load, braked/unbraked (kg)	-/-

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently



Mercedes-Benz

SL-Class Roadster SL 300.

applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



SL-Class Roadster SL 350.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	V6
Displacement (cm ³)	3.498
Rated output (35) 1)	232 /6.500
Rated torque (Nm @ rpm) 1)	360/4.900
Compression ratio	11,7 : 1
Acceleration 0-100 km/h (s)	6,2
Top speed (km/h)	250

Power transmission (7G-TRONIC)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,27

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	80/10
Fuel consumption, urban (l/100km) 2)	13,8-13,8
Fuel consumption, extra-urban (l/100km) 2)	7,2-7,2
Fuel consumption, combined (l/100km) 2)	9,7-9,7
CO ₂ emissions combined (g/km) 2)	226-226
Cd value	0,30
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Single tube gas pressure/Coil spring, Single tube gas pressure
Tyres/wheels, front	255/45 R 17
Tyres/wheels, rear	255/45 R 17
Steering	hydraulic rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	1.825/295
Perm. gross vehicle weight (kg)	2.120
Max. roof load (kg)	75
Boot capacity (VDA) (l)	235-339
Turning circle (m)	11,04
perm. trailer load, braked/unbraked (kg)	-/-

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

SL-Class Roadster SL 350.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



SL-Class Roadster SL 500.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	V8
Displacement (cm ³)	5.461
Rated output (35) 1)	285 /6.000
Rated torque (Nm @ rpm) 1)	530/2.800 - 4.800
Compression ratio	10,5 : 1
Acceleration 0-100 km/h (s)	5,4
Top speed (km/h)	250

Power transmission (7G-TRONIC)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,65

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	80/10
Fuel consumption, urban (l/100km) 2)	17,3-17,3
Fuel consumption, extra-urban (l/100km) 2)	8,4-8,4
Fuel consumption, combined (l/100km) 2)	11,6-11,6
CO ₂ emissions combined (g/km) 2)	272-272
Cd value	0,30
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure/Coil spring, Double-tube gas pressure
Tyres/wheels, front	255/40 R 18
Tyres/wheels, rear	255/40 R 18
Steering	hydraulic rack-and-pinion steering system
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	1.910/295
Perm. gross vehicle weight (kg)	2.205
Max. roof load (kg)	75
Boot capacity (VDA) (l)	235-339
Turning circle (m)	11,04
perm. trailer load, braked/unbraked (kg)	-/-

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

SL-Class Roadster SL 500.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



SL-Class Roadster SL 600.

Engine and performance (5-speed automatic with Touchshift)	
Arrangement/no. of cylinders	V12
Displacement (cm ³)	5.513
Rated output (35) 1)	380 /5.000
Rated torque (Nm @ rpm) 1)	830/1.900 - 3.500
Compression ratio	9,0 : 1
Acceleration 0-100 km/h (s)	4,5
Top speed (km/h)	250

Power transmission (5-speed automatic with Touchshift)	
Drive system	Rear-wheel drive
Transmission	5-speed automatic with Touchshift
Ratios	3,60/2,19/1,41/1,00/0,83/-/-/R1 3,17/R2 1,93
Final-drive ratio	2,65

Fuel and emissions (5-speed automatic with Touchshift)	
Tank capacity/reserve (l)	80/10
Fuel consumption, urban (l/100km) 2)	21,1-21,1
Fuel consumption, extra-urban (l/100km) 2)	9,6-9,6
Fuel consumption, combined (l/100km) 2)	13,9-13,9
CO2 emissions combined (g/km) 2)	326-326
Cd value	0,31
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure/Coil spring, Double-tube gas pressure
Tyres/wheels, front	255/40 R 18
Tyres/wheels, rear	285/35 R 18
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, internally ventilated

Quantities, dimensions and weights (5-speed automatic with Touchshift)	
Kerb weight/payload (kg) 3)	2.045/275
Perm. gross vehicle weight (kg)	2.320
Max. roof load (kg)	75
Boot capacity (VDA) (l)	235-339
Turning circle (m)	11,04
perm. trailer load, braked/unbraked (kg)	-/-

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently



Mercedes-Benz

SL-Class Roadster SL 600.

applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



SL-Class Roadster SL 63 AMG.

Engine and performance (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Arrangement/no. of cylinders	V8
Displacement (cm ³)	6.208
Rated output (35) 1)	386 /6.800
Rated torque (Nm @ rpm) 1)	630/5.200
Compression ratio	11,3 : 1
Acceleration 0-100 km/h (s)	4,6
Top speed (km/h)	250

Power transmission (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Drive system	Rear-wheel drive
Transmission	AMG SPEEDSHIFT MCT 7-speed sports transmission
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,06

Fuel and emissions (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Tank capacity/reserve (l)	80,0/14
Fuel consumption, urban (l/100km) 2)	21,7-21,7
Fuel consumption, extra-urban (l/100km) 2)	9,7-9,7
Fuel consumption, combined (l/100km) 2)	14,1-14,1
CO2 emissions combined (g/km) 2)	328-328
Cd value	0,30
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure/Coil spring, Double-tube gas pressure
Tyres/wheels, front	255/35 R 19
Tyres/wheels, rear	285/30 R 19
Steering	hydraulic rack-and-pinion speed-sensitive steering without power steering regulation
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated and perforated

Quantities, dimensions and weights (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Kerb weight/payload (kg) 3)	1.970/255
Perm. gross vehicle weight (kg)	2.225
Max. roof load (kg)	75
Boot capacity (VDA) (l)	235-339
Turning circle (m)	11,04
perm. trailer load, braked/unbraked (kg)	-/-

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently



Mercedes-Benz

SL-Class Roadster SL 63 AMG.

applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly