



## CLS-Class Coupé CLS 250 CDI BlueEFFICIENCY.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	L4
Model variant number	218303
Restriction code	, 0-802 Model year 2012
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.143
Rated output (kW [PS] @ rpm) 1)	150 [204]/4.200
Rated torque (Nm @ rpm) 1)	500/1.600 - 1.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	7,5
Top speed (km/h)	242

Power transmission (7G-TRONIC)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,473

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban (l/100km) 2)	6,5-6,4
Fuel consumption, extra-urban (l/100km) 2)	4,5-4,4
Fuel consumption, combined (l/100km) 2)	5,3-5,1
CO2 emissions combined (g/km) 2)	138-134
32259	A
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering	no details
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	22/28/28

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	1.785/485
Perm. gross vehicle weight (kg)	2.270
Max. roof load (kg)	100



Mercedes-Benz

## CLS-Class Coupé CLS 250 CDI BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	11,27
Vehicle length (mm)	4.940
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.416
Cd value	0,26
Track width, front (mm)	1.596
Track width, rear (mm)	1.624
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## CLS-Class Coupé CLS 350 CDI BlueEFFICIENCY.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	V6
Model variant number	218323
Restriction code	, 0-802 Model year 2012
Market launch	2011.09
Displacement (cm <sup>3</sup> )	2.987
Rated output (kW [PS] @ rpm) 1)	195 [265]/3.800
Rated torque (Nm @ rpm) 1)	620/1.600 - 2.400
Compression ratio	15,5 : 1
Acceleration 0-100 km/h (s)	6,2
Top speed (km/h)	250

Power transmission (7G-TRONIC)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,473

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	7,8-7,8
Fuel consumption, extra-urban (l/100km) 2)	5,1-5,0
Fuel consumption, combined (l/100km) 2)	6,1-6,0
CO2 emissions combined (g/km) 2)	160-159
32259	B
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering	no details
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	22/28/28

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	1.815/485
Perm. gross vehicle weight (kg)	2.300
Max. roof load (kg)	100



Mercedes-Benz

## CLS-Class Coupé CLS 350 CDI BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	11,27
Vehicle length (mm)	4.940
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.416
Cd value	0,28
Track width, front (mm)	1.596
Track width, rear (mm)	1.624
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## CLS-Class Coupé CLS 350 BlueEFFICIENCY.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	V6
Model variant number	218359
Restriction code	, 0-802 Model year 2012, 0-B03 - ECO start/stop function
Market launch	2011.09
Displacement (cm <sup>3</sup> )	3.498
Rated output (kW [PS] @ rpm) 1)	225 [306]/6.500
Rated torque (Nm @ rpm) 1)	370/3.500 - 5.250
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	6,1
Top speed (km/h)	250

Power transmission (7G-TRONIC)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,823

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	9,5-9,1
Fuel consumption, extra-urban (l/100km) 2)	5,6-5,4
Fuel consumption, combined (l/100km) 2)	7,0-6,8
CO2 emissions combined (g/km) 2)	164-159
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Coil spring, Single-tube gas pressure with SDD
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering	no details
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	22/28/28

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	1.735/485
Perm. gross vehicle weight (kg)	2.220
Max. roof load (kg)	100



Mercedes-Benz

## CLS-Class Coupé CLS 350 BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	11,27
Vehicle length (mm)	4.940
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.416
Cd value	0,27
Track width, front (mm)	1.596
Track width, rear (mm)	1.624
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## CLS-Class Coupé CLS 500 BlueEFFICIENCY.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	V8
Model variant number	218373
Restriction code	, 0-802 Model year 2012
Market launch	2011.09
Displacement (cm <sup>3</sup> )	4.663
Rated output (kW [PS] @ rpm) 1)	300 [408]/5000-5.750
Rated torque (Nm @ rpm) 1)	600/1.600 - 4.750
Compression ratio	10,5 : 1
Acceleration 0-100 km/h (s)	5,2
Top speed (km/h)	250

Power transmission (7G-TRONIC)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,473

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban (l/100km) 2)	12,5-12,5
Fuel consumption, extra-urban (l/100km) 2)	6,9-6,9
Fuel consumption, combined (l/100km) 2)	9,0-9,0
CO2 emissions combined (g/km) 2)	209-209
32259	E
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Air spring, Damper with damper valve/Air spring, Damper with damper valve
Tyres/wheels, front	255/40 R 18
Tyres/wheels, rear	255/40 R 18
Steering	no details
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	22/28/28

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	1.890/485
Perm. gross vehicle weight (kg)	2.375
Max. roof load (kg)	100



Mercedes-Benz

## CLS-Class Coupé CLS 500 BlueEFFICIENCY.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	11,27
Vehicle length (mm)	4.940
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.404
Cd value	0,28
Track width, front (mm)	1.598
Track width, rear (mm)	1.629
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## CLS-Class Coupé CLS 63 AMG.

Engine and performance (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Arrangement/no. of cylinders	V8
Model variant number	218374
Restriction code	, 0-802 Model year 2012
Market launch	2011.09
Displacement (cm <sup>3</sup> )	5.461
Rated output (kW [PS] @ rpm) 1)	386 [525]/5250-5.750
Rated torque (Nm @ rpm) 1)	700/1.700 - 5.000
Compression ratio	10,0 : 1
Acceleration 0-100 km/h (s)	4,4
Top speed (km/h)	250

Power transmission (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Drive system	Rear-wheel drive
Transmission	AMG SPEEDSHIFT MCT 7-speed sports transmission
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,65

Fuel and emissions (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Tank capacity/reserve (l)	66/14
Fuel consumption, urban (l/100km) 2)	13,9-13,9
Fuel consumption, extra-urban (l/100km) 2)	7,6-7,6
Fuel consumption, combined (l/100km) 2)	9,9-9,9
CO2 emissions combined (g/km) 2)	231-231
32259	F
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Spring strut with coil spring, Monroe CES adjustable damping/Air spring, Monroe CES adjustable damping
Tyres/wheels, front	255/35 ZR 19
Tyres/wheels, rear	285/30 ZR 19
Steering	no details
Front brakes	Compound discs, internally ventilated and perforated
Rear brakes	Compound discs, internally ventilated and perforated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.

Quantities, dimensions and weights (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Kerb weight/payload (kg) 3)	1.870/545
Perm. gross vehicle weight (kg)	2.415
Max. roof load (kg)	100



Mercedes-Benz

## CLS-Class Coupé CLS 63 AMG.

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	11,30
Vehicle length (mm)	4.996
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.406
Cd value	0,30
Track width, front (mm)	1.625
Track width, rear (mm)	1.604
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## CLS-Class Coupé CLS 63 AMG (Performance Package).

Engine and performance (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Arrangement/no. of cylinders	V8
Model variant number	218374
Restriction code	, 0-802 Model year 2012, 0-P30 - Performance package
Market launch	2011.09
Displacement (cm <sup>3</sup> )	5.461
Rated output (kW [PS] @ rpm) 1)	410 [557]/5250-5.750
Rated torque (Nm @ rpm) 1)	800/2.000 - 4.500
Compression ratio	10,0 : 1
Acceleration 0-100 km/h (s)	4,3
Top speed (km/h)	250

Power transmission (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Drive system	Rear-wheel drive
Transmission	AMG SPEEDSHIFT MCT 7-speed sports transmission
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,65

Fuel and emissions (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Tank capacity/reserve (l)	66/14
Fuel consumption, urban (l/100km) 2)	13,9-13,9
Fuel consumption, extra-urban (l/100km) 2)	7,6-7,6
Fuel consumption, combined (l/100km) 2)	9,9-9,9
CO2 emissions combined (g/km) 2)	231-231
32259	F
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Spring strut with coil spring, Monroe CES adjustable damping/Air spring, Monroe CES adjustable damping
Tyres/wheels, front	255/35 ZR 19
Tyres/wheels, rear	285/30 ZR 19
Steering	no details
Front brakes	Compound discs, internally ventilated and perforated
Rear brakes	Compound discs, internally ventilated and perforated

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.

Quantities, dimensions and weights (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Kerb weight/payload (kg) 3)	1.870/545
Perm. gross vehicle weight (kg)	2.415
Max. roof load (kg)	100



Mercedes-Benz

## CLS-Class Coupé CLS 63 AMG (Performance Package).

Boot capacity (VDA) min/max (l)	
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	11,30
Vehicle length (mm)	4.996
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.406
Cd value	0,30
Track width, front (mm)	1.625
Track width, rear (mm)	1.605
Wheelbase (mm)	2.874

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly