



Mercedes-Benz

SLK-Class Roadster SLK 250 CDI BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	172403
Restriction code	
Market launch	2011.12
Displacement (cm ³)	2.143
Rated output (kW [PS] @ rpm) 1)	150 [204]/4.200
Rated torque (Nm @ rpm) 1)	500/1.600
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	6,7
Top speed (km/h)	243

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,466

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	60/8,0
Fuel consumption, urban (l/100km) 2)	6,2-6,1
Fuel consumption, extra-urban (l/100km) 2)	4,3-4,1
Fuel consumption, combined (l/100km) 2)	5,0-4,9
CO2 emissions combined (g/km) 2)	132-128
32259	A
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure/Coil spring, Single tube gas pressure
Tyres/wheels, front	205/55 R 16 91 W
Tyres/wheels, rear	225/50 R 16 92 W
Steering	hydraulic rack-and-pinion steering system without power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.



SLK-Class Roadster SLK 250 CDI BlueEFFICIENCY.

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.590/315
Perm. gross vehicle weight (kg)	1.905
Max. roof load (kg)	k. A.
Boot capacity (VDA) min/max (l)	225/335
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	10,52
Vehicle length (mm)	4.134
Vehicle width (mm)	1.817
Vehicle height at kerb weight (mm)	1.301
Cd value	0,30
Track width, front (mm)	1.558
Track width, rear (mm)	1.548
Wheelbase (mm)	2.430

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



SLK-Class Roadster SLK 200 BlueEFFICIENCY.

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Model variant number	172448
Restriction code	0-B03 - ECO start/stop function
Market launch	2011.03
Displacement (cm ³)	1.796
Rated output (kW [PS] @ rpm) 1)	135 [184]/5.250
Rated torque (Nm @ rpm) 1)	270/1.800 - 4.600
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	7,3
Top speed (km/h)	240

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	172448
Restriction code	0-B03 - ECO start/stop function
Market launch	2011.03
Displacement (cm ³)	1.796
Rated output (kW [PS] @ rpm) 1)	135 [184]/5.250
Rated torque (Nm @ rpm) 1)	270/1.800 - 4.600
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	7,0
Top speed (km/h)	237

Power transmission (6-speed (manual))	
Drive system	Rear-wheel drive
Transmission	6-speed (manual)
Ratios	4,99/2,82/1,78/1,25/1,00/0,82/-/R1 4,54/R2 -
Final-drive ratio	2,866

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,066

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	60/8,0
Fuel consumption, urban (l/100km) 2)	9,3-8,9
Fuel consumption, extra-urban (l/100km) 2)	5,3-5,0
Fuel consumption, combined (l/100km) 2)	6,8-6,4
CO2 emissions combined (g/km) 2)	158-149
32259	C
Emissions category	Euro 5



SLK-Class Roadster SLK 200 BlueEFFICIENCY.

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	60/8,0
Fuel consumption, urban (l/100km) 2)	8,6-8,3
Fuel consumption, extra-urban (l/100km) 2)	5,3-4,9
Fuel consumption, combined (l/100km) 2)	6,5-6,1
CO2 emissions combined (g/km) 2)	151-142
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure/Coil spring, Single tube gas pressure
Tyres/wheels, front	205/55 R 16 91 V
Tyres/wheels, rear	205/55 R 16 91 V
Steering	hydraulic rack-and-pinion steering system without power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	13/23/23

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.435/315
Perm. gross vehicle weight (kg)	1.750
Max. roof load (kg)	k. A.
Boot capacity (VDA) min/max (l)	225/335
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	10,52
Vehicle length (mm)	4.134
Vehicle width (mm)	1.810
Vehicle height at kerb weight (mm)	1.301
Cd value	0,30
Track width, front (mm)	1.559
Track width, rear (mm)	1.565
Wheelbase (mm)	2.430

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.470/315
Perm. gross vehicle weight (kg)	1.785
Max. roof load (kg)	k. A.
Boot capacity (VDA) min/max (l)	225/335
perm. trailer load, braked/unbraked (kg)	-/-



Mercedes-Benz

SLK-Class Roadster SLK 200 BlueEFFICIENCY.

Permissible drawbar load (kg)	-
Turning circle (m)	10,52
Vehicle length (mm)	4.134
Vehicle width (mm)	1.810
Vehicle height at kerb weight (mm)	1.301
Cd value	0,30
Track width, front (mm)	1.559
Track width, rear (mm)	1.565
Wheelbase (mm)	2.430

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



SLK-Class Roadster SLK 250 BlueEFFICIENCY.

Engine and performance (6-speed (manual))	
Arrangement/no. of cylinders	L4
Model variant number	172447
Restriction code	0-B03 - ECO start/stop function
Market launch	2011.12
Displacement (cm ³)	1.796
Rated output (kW [PS] @ rpm) 1)	150 [204]/5.500
Rated torque (Nm @ rpm) 1)	310/2.000 - 4.300
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	6,5
Top speed (km/h)	244

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	172447
Restriction code	0-B03 - ECO start/stop function
Market launch	2011.03
Displacement (cm ³)	1.796
Rated output (kW [PS] @ rpm) 1)	150 [204]/5.500
Rated torque (Nm @ rpm) 1)	310/2.000 - 4.300
Compression ratio	9,3 : 1
Acceleration 0-100 km/h (s)	6,6
Top speed (km/h)	243

Power transmission (6-speed (manual))	
Drive system	Rear-wheel drive
Transmission	6-speed (manual)
Ratios	4,46/2,61/1,72/1,25/1,00/0,84/-/R1 4,06/R2 -
Final-drive ratio	3,266

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,066

Fuel and emissions (6-speed (manual))	
Tank capacity/reserve (l)	60/8,0
Fuel consumption, urban (l/100km) 2)	9,8-9,5
Fuel consumption, extra-urban (l/100km) 2)	5,8-5,3
Fuel consumption, combined (l/100km) 2)	7,3-6,9
CO2 emissions combined (g/km) 2)	169-160
32259	D
Emissions category	Euro 5



Mercedes-Benz

SLK-Class Roadster SLK 250 BlueEFFICIENCY.

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	60/8,0
Fuel consumption, urban (l/100km) 2)	8,7-8,4
Fuel consumption, extra-urban (l/100km) 2)	5,4-5,0
Fuel consumption, combined (l/100km) 2)	6,6-6,2
CO2 emissions combined (g/km) 2)	153-144
32259	C
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure/Coil spring, Single tube gas pressure
Tyres/wheels, front	225/45 R 17 91 W
Tyres/wheels, rear	245/40 R 17 91 W
Steering	hydraulic rack-and-pinion steering system without power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	13/23/23

Quantities, dimensions and weights (6-speed (manual))	
Kerb weight/payload (kg) 3)	1.475/315
Perm. gross vehicle weight (kg)	1.790
Max. roof load (kg)	k. A.
Boot capacity (VDA) min/max (l)	225/335
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	10,52
Vehicle length (mm)	4.134
Vehicle width (mm)	1.817
Vehicle height at kerb weight (mm)	1.303
Cd value	0,32
Track width, front (mm)	1.551
Track width, rear (mm)	1.568
Wheelbase (mm)	2.430

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.500/315
Perm. gross vehicle weight (kg)	1.815
Max. roof load (kg)	k. A.
Boot capacity (VDA) min/max (l)	225/335
perm. trailer load, braked/unbraked (kg)	-/-



Mercedes-Benz

SLK-Class Roadster SLK 250 BlueEFFICIENCY.

Permissible drawbar load (kg)	-
Turning circle (m)	10,52
Vehicle length (mm)	4.134
Vehicle width (mm)	1.817
Vehicle height at kerb weight (mm)	1.303
Cd value	0,32
Track width, front (mm)	1.551
Track width, rear (mm)	1.568
Wheelbase (mm)	2.430

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



SLK-Class Roadster SLK 350 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	172457
Restriction code	
Market launch	2011.03
Displacement (cm ³)	3.498
Rated output (kW [PS] @ rpm) 1)	225 [306]/6.500
Rated torque (Nm @ rpm) 1)	370/3.500 - 5.250
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	5,6
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive system	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	3,066

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	60/8,0
Fuel consumption, urban (l/100km) 2)	9,9-9,9
Fuel consumption, extra-urban (l/100km) 2)	5,5-5,5
Fuel consumption, combined (l/100km) 2)	7,1-7,1
CO2 emissions combined (g/km) 2)	167-167
32259	D
Emissions category	Euro 5

Chassis and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure/Coil spring, Single tube gas pressure
Tyres/wheels, front	225/45 R 17 91 W
Tyres/wheels, rear	245/40 R 17 91 W
Steering	hydraulic rack-and-pinion steering system without power steering regulation
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	14/26/23



SLK-Class Roadster SLK 350 BlueEFFICIENCY.

Quantities, dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 3)	1.540/315
Perm. gross vehicle weight (kg)	1.855
Max. roof load (kg)	k. A.
Boot capacity (VDA) min/max (l)	225/335
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	10,52
Vehicle length (mm)	4.134
Vehicle width (mm)	1.817
Vehicle height at kerb weight (mm)	1.303
Cd value	0,32
Track width, front (mm)	1.551
Track width, rear (mm)	1.568
Wheelbase (mm)	2.430

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

SLK-Class Roadster SLK 55 AMG.

Engine and performance ()	
Arrangement/no. of cylinders	V8
Model variant number	172475
Restriction code	
Market launch	2012.01
Displacement (cm ³)	5.461
Rated output (kW [PS] @ rpm) 1)	310 [421]/6.800
Rated torque (Nm @ rpm) 1)	540/4.500
Compression ratio	12,6 : 1
Acceleration 0-100 km/h (s)	4,6
Top speed (km/h)	250

Power transmission ()	
Drive system	Rear-wheel drive
Transmission	
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,82

Fuel and emissions ()	
Tank capacity/reserve (l)	70/9
Fuel consumption, urban (l/100km) 2)	12,0-12,0
Fuel consumption, extra-urban (l/100km) 2)	6,2-6,2
Fuel consumption, combined (l/100km) 2)	8,4-8,4
CO2 emissions combined (g/km) 2)	195-195
32259	E
Emissions category	Euro 5

Chassis and steering	
Front axle	Three-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Coil spring, Double-tube gas pressure/Coil spring, Single tube gas pressure
Tyres/wheels, front	235/40 R 18
Tyres/wheels, rear	255/35 R 18
Steering	hydraulic rack-and-pinion steering system with power steering regulation
Front brakes	Sliding frame-type callipers with compound brake discs
Rear brakes	Discs

Vehicle identification	
Insurance rating	
Insurance category liability/FC/partial	k. A./k. A./k. A.



SLK-Class Roadster SLK 55 AMG.

Quantities, dimensions and weights ()	
Kerb weight/payload (kg) 3)	1.610/300
Perm. gross vehicle weight (kg)	1.910
Max. roof load (kg)	-
Boot capacity (VDA) min/max (l)	225/335
perm. trailer load, braked/unbraked (kg)	-/-
Permissible drawbar load (kg)	-
Turning circle (m)	10,53
Vehicle length (mm)	4.146
Vehicle width (mm)	1.817
Vehicle height at kerb weight (mm)	1.300
Cd value	0,34
Track width, front (mm)	1.549
Track width, rear (mm)	1.567
Wheelbase (mm)	2.430

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly