



G-Class Off-roaders G 350 BlueTEC Cabriolet.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	V6
Displacement (cm ³)	2.987
Rated output (35) 1)	155 /3.400
Rated torque (Nm @ rpm) 1)	540/1.600 - 2.400
Compression ratio	17,7 : 1
Acceleration 0-100 km/h (s)	8,8
Top speed (km/h)	175

Power transmission (7G-TRONIC)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 -
Final-drive ratio	4,38

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	96/20
Fuel consumption, urban (l/100km) 2)	13,6-13,6
Fuel consumption, extra-urban (l/100km) 2)	9,8-9,8
Fuel consumption, combined (l/100km) 2)	11,2-11,2
CO2 emissions combined (g/km) 2)	295-295
Cd value	0,54
Emissions category	Euro 5

Chassis and steering	
Front axle	Trailing link+Panhard rod
Rear axle	Trailing link+Panhard rod
Springs, front/rear	Coil spring, Gas pressure/Coil spring, Gas pressure
Tyres/wheels, front	265/70 R 16
Tyres/wheels, rear	265/70 R 16
Steering	no details
Front brakes	Discs, solid
Rear brakes	Discs, solid

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	2.320/530
Perm. gross vehicle weight (kg)	2.850
Max. roof load (kg)	150
Boot capacity (VDA) (l)	k. A.
Turning circle (m)	11,30
perm. trailer load, braked/unbraked (kg)	750/2.850

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the



Mercedes-Benz

G-Class Off-rovers G 350 BlueTEC Cabriolet.

different vehicle models. They do not constitute part of the product offer

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



G-Class Off-rovers G 500 Cabriolet.

Engine and performance (7G-TRONIC)	
Arrangement/no. of cylinders	V8
Displacement (cm ³)	5.461
Rated output (35) 1)	285 /6.000
Rated torque (Nm @ rpm) 1)	530/2.800 - 4.800
Compression ratio	10,7 : 1
Acceleration 0-100 km/h (s)	5,9
Top speed (km/h)	210

Power transmission (7G-TRONIC)	
Drive system	Permanent four-wheel drive
Transmission	7G-TRONIC
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 -
Final-drive ratio	4,38

Fuel and emissions (7G-TRONIC)	
Tank capacity/reserve (l)	96/20
Fuel consumption, urban (l/100km) 2)	20,0-20,0
Fuel consumption, extra-urban (l/100km) 2)	11,9-11,9
Fuel consumption, combined (l/100km) 2)	14,9-14,9
CO2 emissions combined (g/km) 2)	348-348
Cd value	0,54
Emissions category	Euro 5

Chassis and steering	
Front axle	Trailing link+Panhard rod
Rear axle	Trailing link+Panhard rod
Springs, front/rear	Coil spring, Gas pressure/Coil spring, Gas pressure
Tyres/wheels, front	265/60 R 18 100H
Tyres/wheels, rear	265/60 R 18 100H
Steering	no details
Front brakes	Discs, internally ventilated
Rear brakes	Discs, solid

Quantities, dimensions and weights (7G-TRONIC)	
Kerb weight/payload (kg) 3)	2.335/515
Perm. gross vehicle weight (kg)	2.850
Max. roof load (kg)	150
Boot capacity (VDA) (l)	k. A.
Turning circle (m)	11,30
perm. trailer load, braked/unbraked (kg)	750/2.850

1) Rated output figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring processes (Directive 80/1268/EEC in the currently applicable version). The figures are not based on an individual vehicle and are provided solely for purposes of comparison between the different vehicle models. They do not constitute part of the product offer



Mercedes-Benz

G-Class Off-rovers G 500 Cabriolet.

3) Figures according to Directive 92 / 21 / EC, version 95 / 48 / EC (kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg) for standard - specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly